



### Typical Inspection Data:

|                |                         |
|----------------|-------------------------|
| Density @ 20°C | 1.074 g/cm <sup>3</sup> |
| Appearance     | Clear green/blue liquid |

## Super Coldmaster

### Ready to Use

#### Recommended by Comma for applications requiring:

Based on concentrate that conforms to:  
BS6580:2010; AFNOR NFR 15-601

#### Product Features:

- A Mono Ethylene Glycol (MEG) based engine coolant.
- Suitable for use in all types of vehicle requiring an MEG coolant.
- Suitable for Ferrous and Aluminium engines.
- -36 Winter protection.
- +45 Summer protection.
- 2 years full protection.
- Helps prevent winter freezing and summer boil over. Also improves heat transfer.
- NAP (Nitrite, Phosphate and Amine) free.

#### Directions for use:

- Ready to use, but for maximum protection first drain and flush cooling system.
- For full protection do not mix with other fluids.
- Minor spills should be soaked up with absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.

#### Handling:

- Remove spills from paintwork immediately.
- Keep away from foodstuffs and oxidising agents.
- Store in airtight container.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

#### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 23-06-2021

Moove Lubricants Ltd. Dering Way, Gravesend, Kent DA12 2QX, England.

Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com [www.CommaOil.com](http://www.CommaOil.com)