



Eurolite 10W-40

Semi Synthetic

Official Approvals:

Approved under VW standard VW 501 01 and VW 505 00

Recommended by Comma for applications requiring:

RN0700, RN0710; PSA B71 2300; MB 229.3; ACEA A3/B4; API SN CF

Product Features:

- Semi synthetic, high performance 10W-40 oil, suitable for petrol and diesel vehicles including those with fuel injected and multivalved engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20°C	0.865 g/cm ³
Viscosity @ 100°C	13.7 cSt
Viscosity @ 40°C	92 cSt
Viscosity Index	151
Viscosity CCS @ -25°C	6000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.3%
Zinc	0.12%
Calcium	0.30%
Phosphorus	0.11%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

UPDATED: 16-11-2018