



EP80W-90 GL-5

Mineral

Product Features:

- Extreme pressure gear oil for manual gearboxes.
- Recommended by Comma for applications requiring an 80W-90 or 85W-90, API GL-5, GL-4 oil.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com.

Typical Inspection Data:

Density @ 20 °C	0.875 g/cm ³
Viscosity @ 100 °C	14.0 cSt
Viscosity @ 40 °C	129 cSt
Phosphorus	0.02%
Colour	Brown
Pour Point	-30 °C

Performance Profile:

Recommended by Comma for certain applications where an 80W-90 or 85W-90 API GL-5, GL-4 oil is specified. Suitable for use where the following specifications are called for:

API GL-5; Ford M2C197-A; MB 235.0

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Modified 11.01.2021

Moove Lubricants Ltd. Dering Way, Gravesend, Kent DA12 2QX, England.
Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com www.CommaOil.com

Typical Inspection Data are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.
All products may not be available locally. For more information, contact your local Cosan contact or visit www.CommaOil.com.