



Typical Inspection Data:

Density @ 20 °C	0.842 g/cm ³
Viscosity @ 100 °C	6.3 cSt
Viscosity @ 40 °C	32 cSt
Phosphorus	0.02%
Colour	Red
Pour Point	-45 °C

Performance Profile:

Recommended by Comma for certain Aisin-Warner automatic transmissions in Ford, Saab, Toyota, Volkswagen & Volvo vehicles. Suitable for use where the following specifications are called for:

JWS 3309; VW G 055 025; Volvo 1161540; Toyota Type T-IV;
Ford WSS-M2C924-A

ASW Semi Synthetic

Product Features:

- Specific to Aisin-Warner automatic transmissions.
- Suitable for a number of applications including Saab & Volvo.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Modified 11.01.2021

Moove Lubricants Ltd. Dering Way, Gravesend, Kent DA12 2QX, England.
Tel: +44 (0)1474 564 311, Fax: +44(0)1474 333 000 Email: sales@commaoil.com www.CommaOil.com

Typical Inspection Data are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.
All products may not be available locally. For more information, contact your local Cosan contact or visit www.CommaOil.com.