



TransFlow XP 20W-50

Mineral

Recommended by Comma for applications requiring:

ACEA A3/B3 E3-Level; API CF CG-4 SL;
MB 228.3, MB 229.1

Product Features:

- Mineral, 20W-50 oil, suitable for petrol and diesel vehicles including those with fuel injected, multivalved and turbo charged engines.
- For engine protection.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:

Density @ 20°C	0.877 g/cm ³
Viscosity @ 100°C	18.6 cSt
Viscosity @ 40°C	170 cSt
Viscosity Index	123
Viscosity CCS @ -15°C	8300 cP
T.B.N.	8.7 mg KOH/g
Sulphated Ash Mass	1.3%
Zinc	0.11%
Calcium	0.30%
Phosphorus	0.10%
Colour	Brown
Flash Point	230°C
Pour Point	-33°C

UPDATED: 17-07-2019