



Typical Inspection Data:

Appearance

Hydrocarbon odour

Carb Clean

Product Features:

- A powerful blended solvent specifically designed for removing spent fuel deposits.
- Easily dissolves oils, greases, gums and carbon deposits from fuel delivery areas.

Direction of use:

1. Ensure engine is cold & switched off.
2. Remove air cleaner/ filter.
3. Shake can & (with extension tube fitted) apply liberally to exterior of carburettor & linkages. Allow to soak & repeat as necessary.
4. Start engine & spray inside carburettor throat.
5. Switch off ignition & refit air cleaner/ filter.
6. For Automatic Choke, spray both ends of choke valve & vacuum cylinder. Important: Wash off immediately if sprayed on paintwork – may cause streaking.

Handling:

- Caution pressurised container: protect from sunlight and other heat sources.
- Refer to Material Safety Data Sheet.

Shelf Life:

- 3 years from date of manufacture.
- Manufacture date can be identified as follows:

1st Letter-Year	2nd Letter-Month	2 Numbers -Day	Time
2020	A	Jan	A
2021	B	Feb	B
2022	C	Mar	C
2023	D	Apr	D
2024	E	May	E
2025	F	Jun	F
2026	G	Jul	G
2027	H	Aug	H
2028	J	Sep	J
2029	K	Oct	K
2030	L	Nov	L
2031	M	Dec	M

Number denotes the day of the Month

Time in 24 hour format: hour and minutes e.g. 16:05

UPDATED: 29-09-2021