



Typical Inspection Data:

| | |
|-------------------|-------------------------|
| Density @ 20°C | 0.873 g/cm ³ |
| Viscosity @ 100°C | 8.5 cSt |
| Colour | Red |

2 Stroke Racing

Fully Synthetic

Recommended by Comma for applications requiring:

JASO FC/FD, ISO-L-EGC/EGD, API TC, Rotax 253

Product Features:

- Premium low ash fully-synthetic oil for all type of two stroke petrol engines (motorcycles, mopeds, cars, lawnmowers etc.) requiring an oil of this type and quality level.
- Tailored for use in applications involving high engine temperatures and speeds and high torque.
- Particularly suitable for demanding applications such as go-karts, snowmobiles and chain saws.
- Fully-synthetic formulation incorporating poly-iso-butylene (PIB) and esters to ensure good lubricity and very low smoke levels.
- Excellent at preventing ring sticking and exhaust valve blocking.

Important:

- The engine manufacturer's recommendations on mixture ratios should be observed.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 27-11-2020